

Honda Pump WB20XK2

FEATURES:

- ◆ Multi-purpose 2" pump
- ◆ Designed for pumping industrial and agricultural chemicals
- ◆ Easy starting Honda OHV commercial engine
- ◆ 220 gal./min capacity
- ◆ Thermoplastic pump housing for chemical capability



EU3000 Handi	Specification
Engine	Honda GX160
Displacement	163cc
Bore & Stroke	2.7" x 1.8"
Compression Ratio	8.5:1
Oil Alert	Standard
Pump Type	Multi-purpose Centrifugal Self-priming
Volute	Rigid Mounted Fiberglass reinforced polyester
Impeller	Fiberglass reinforced polyester
Mechanical Seal	Carbon/Ceramic
Priming Time	65 sec @ 16.4 ft.
Drive System	Direct
Discharge Capacity	220 gals. / min.
Suction Port Diameter	2" NPT
Discharge Port Diameter	2" NPT
Total Head Lift	105 ft.
Suction Head Lift	26 ft.
Maximum Pressure	45 psi
Solids Handling	N/A
Dimensions (LxWxH)	20.5" x 15.7" x 17.7"
Dry Weight	56 lbs.
Strainer Part	# 78325-YE0-003
Residential Warranty	3 years
Commercial Warranty	3 year