

# HONDA PUMP WMP20XA

## APPROVED PUMPING APPLICATIONS

### INDUSTRIAL CHEMICALS

Acetic Acid, 20%	Ferric Nitrate	Nickel Sulfate	Sodium Chlorate
Aluminum Sulfate	Ferric Sulfate	Oleic Acid	Sodium Chloride
Ammonium Nitrate	Ferrous Sulfate	Phosphoric Acid, 0-80%	Sodium Nitrate
Ammonium Sulfate	Formaldehyde, 40%	Potassium Carbonate	Sodium Silicate
Barium Sulfate	Glycerine (Glycerol)	Potassium Chloride	Sodium Sulfate
Borax (Sodium Borate)	Lactic Acid	Potassium Nitrate	Stearic Acid
Calcium Chloride*	Lead Acetate	Potassium Sulfate	Sulfuric Acid, 0-29%
Citric Acid	Magnesium Chloride	Soaps (neutral)	Tartaric Acid
Copper Sulfate	Magnesium Nitrate	Sodium Acetate	Vinegar
Detergents (general)	Magnesium Sulfate	Sodium Bicarbonate	Water (clear)
Ethylene Glycol	Maleic Acid	Sodium Bisulfate	Water (salt)
Fatty Acids	Nickel Chloride	Sodium Carbonate, 10%	Zinc, Sulfate

\*Temperature does not exceed 80°F

### AGRICULTURAL CHEMICALS

Aatrex	Dual	Phosphoric Acid Solutions
Amiben	Eradicane	Poly-N
Ammonium Thiosulfate	Extrazine	Ranger
Avenge	Larsban	Round-up
Banvel	Lasso	Sutan
Basagran	URAN Solutions	Treflan
Bicep	Modown	Vernam
Bladex	N-Serve 24	

- ◆ Do not use the WMP20XA for pumping liquids for human consumption.
- ◆ After each use, drain pump housing into a suitable container and flush with fresh water.
- ◆ The temperature operating range of the pump is between 20 and 130°F